

Binocular brightfield microscope, 1000x, IOS N-PLAN objectives

Main Body	Type	Upright
	Construction material	Aluminum die-cast
	with trasportation handle	Yes
	Internal prism	Glass prism
	Optical system	Infinity
	Optics with anti-fungus treatment	Yes

Head	Type	Binocular
	Construction	Siedentopf
	Inclination	30°
	Rotation	360°
	Fixing screw for eyepieces	Yes
	Diopter adjustment	On both tubes
	Diopter compensation	±5
	Interpupillary distance (mm)	48-75
	Tube inner diameter (mm)	23

Eyepieces	Magnification	10x
	Field number (mm)	20
	High eyepoint (for glass wearers)	Yes

Nosepiece	Positions	Quadruple
	Reversed	Yes
	Bi-directional	Yes
	Rotation on ball bearings	Yes
	Objective thread	RMS

Objectives	Type	IOS N-PLAN
	Correction	Plan Achromatic
	Parfocal distance (mm)	DIN 45
	Optical system	Infinity
	Standard magnifications	4x-10x-40x-100x

Stage	Dimensions (mm)	150x140
	Mechanical stage	Rackless
	Material	Anti-scratch painting
	Specimen holder	Yes
	Slide number	1
	Moving range (mm)	75x33
	X-Y movement	Yes
	X-Y Vernier scale	Yes
	Vernier scale accuracy (mm)	0.1
	Type	Double layer
	Right / Left hand	Right
Condenser - Single Position	Type	Abbe
	Numerical aperture (N.A.)	0.9 / 1.25
	Magnification scale for simplified positioning	Yes
	Aperture diaphragm	Iris
	Removable	Yes
	Slot for sliders	Yes
	Slider for phase contrast	Optional
	Slider for darkfield (dry)	Optional
	Centerable	Yes
	Focusable	By rack and pinion
Focusing System	Type	Coaxial coarse & fine
	Focus modes	Coarse & fine
	Coarse total travel (mm)	18
	Fine graduations	100
	Fine total travel (per single rotation) (mm)	0,4
	Fine resolution (µm)	4
	Upper stop to prevent contact	Yes
	Adjustable tension	Yes
Observation Method - Transmitted Light	Brightfield	Yes
	Phase contrast (Positive type)	Optional
	Darkfield	Optional
	Simple polarized light	Optional
Transmitted Illumination	Type	X-LED
	X-LED type	X-LED3
	Light source power (W)	3.6
	Brightness control	Manual
	Kohler illumination	Fixed
	Color Temperature (K)	5,500-5,700
	Lifetime (hours)	> 65,000
	Max. required power (W)	6
Power Supply for Illumination	Type	External
	Microscope connector	Jack, 2.1 mm
	Power plug type	Multi-plug (EU, UK, US)
	Input voltage	100/240 Vac, 50/60 Hz
	Output voltage	5 Vdc 2,5 A
Accessories Included	Dust cover	Yes
	Immersion oil (10ml)	Yes
	Tension adjustment tool	Yes
	User Manual	Digital version (downloadable)

Product Dimensions (overall footprint)	Height (mm)	370
	Width (mm)	235
	Depth (mm)	320

Product Weight	(kg)	6.5